DESCRIPTION APPROVED LTR DATE NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 8901 BODY & FITTINGS: NICKEL PLATED BRASS CONTACT: GOLD PLATED BRASS. DIELECTRIC: PTFE SPRING: NICKEL PLATED SK5 GASKET: RED RUBBER 2. P/N: SR58BLK BOOT: BLK MOLDED PVC 3. P/N: Y-1000 HOUSING: BLK MOLDED NYLON HARDWARE: SS SCREW, NUTS & WASHER CENTER O O RED GROUND O O BLACK 4. P/N: 9275BLK WIRING SCHEMATIC INSULATOR: BLK MOLDED PVC. ALLIGATOR: NICKEL PLATED STEEL. 5. P/N: 9275RED INSULATOR: BLK MOLDED PVC. ALLIGATOR: NICKEL PLATED STEEL. 6. P/N: W-500/0 **→** 1.50 [38.10] **→** 20AWG TINNED COPPER STRANDING -/4\ GROUND 0.080 [2.03] O.D. PVC INSULATION 7. P/N: W-500/2 20AWG TINNED COPPER STRANDING 2.3 [59.31] 0.080 [2.03] O.D. PVC INSULATION MADE IN U.S.A. 8. P/N: C-1000/0 **≠** 9.0 [228.6] ØE−Z−HOOK -\(\sigma\) CENTER 20AWG RG58C/U CABLE 3.0 [76.2] 0.195 [4.95] O.D. PVC INSULATION 1.312 [33.32] -1 & 2 CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. TOLERANCES ARE: FRACTIONS DECIMALS ANGLES APPROVALS DATE ±N/A $.XX \pm N/A \pm N/A$ DRAWN 3/19 R.L. $A \times \dot{N} \pm \dot{N} / A$ BNC MALE TO 9275 MINI GATOR APPROVED BY MATERIAL SEE NOTE LEADS, RG58 CABLE SIZE CODE IDENT NO. DRAWING NO. FINISH REV. B |08505| SEE NOTE **NEXT ASSY** USED ON SCALE APPLICATION DO NOT SCALE DRAWING SHEET 1 OF THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.

MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT, MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.

REVISIONS