REVISIONS DESCRIPTION APPROVED LTR DATE NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 9267-0002 & P/N: 0344 BODY & FITTINGS: NICKEL PLATED BRASS CONTACT: GOLD PLATED BRASS. DIELECTRIC: PTFE SPRING: NICKEL PLATED SK5 SPRING: RED RUBBER WASHER: COPPER, TIN, NICKEL PLATED CSR 2. P/N: 0482 & P/N: 0148/0 & P/N: 0581 HOUSING: BLK MOLDED DELRIN CONTACT: GOLD PLATED BeCu HEAT SHRINK: BLK HEAT SHRINK CENTER O O RED 3. P/N: XHBLK GROUND O O BLACK HOUSING: BLK MOLDED NYLON. CONTACT: NICKEL SILVER ALLOY. WIRING SCHEMATIC SPRING: STAINLESS STEEL 4. P/N: XHRED HOUSING: RED MOLDED NYLON. CONTACT: NICKEL SILVER ALLOY. - 3.3 [82.55] -SPRING: STAINLESS STEEL · 1.7 [42.16] — 5. P/N: W-600/0 18AWG TINNED COPPER STRANDING 0.144 [3.66] O.D. PVC INSULATION 6. P/N: W-600/2 18AWG TINNED COPPER STRANDING 2.01 [51.05] 0.144 [3.66] O.D. PVC INSULATION 0.275 [6.98] — 9.0 [228.6] 3.0 [76.2] 4 CENTER CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES APPROVALS DATE .XX ± DRAWN DESCRIPTION 6/17 R.L. .XXX ± BNC MALE BREAKOUT TO APPROVED BY MATERIAL SEE NOTE. 18AWG XH MACROHOOK LEADS SIZE CODE IDENT NO. DRAWING NO. FINISH REV. SEE NOTE. B | 08505 | **NEXT ASSY** USED ON SCALE APPLICATION DO NOT SCALE DRAWING SHEET 1 OF 1

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.

MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.