REVISIONS DESCRIPTION DATE APPROVED LTR NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 9267-0002 & P/N: 0344 BODY & FITTINGS: NICKEL PLATED BRASS CONTACT: GOLD PLATED BRASS. DIELECTRIC: PTFE SPRING: NICKEL PLATED SK5 SPRING: RED RUBBER WASHER: COPPER, TIN, NICKEL PLATED CSR 2. P/N: 0480 & P/N: 0148/0 & P/N: 0581 HOUSING: BLK MOLDED DELRIN CONTACT: GOLD PLATED BeCu HEAT SHRINK: BLK HEAT SHRINK CENTER O O RED 3. P/N: X100WBLK GROUND O O BLACK HOUSING: BLK MOLDED NYLON. CONTACT: GOLD PLATED BeCu. WIRING SCHEMATIC SPRING: STAINLESS STEEL. 4. P/N: XL1RED **—** 2.25 [57.15] **–** HOUSING: RED MOLDED NYLON. CONTACT: GOLD PLATED BeCu. -<u>/</u>3\GROUND SPRING: STAINLESS STEEL. 1.42 [36.07] 5. P/N: W-500/0 20AWG TINNED COPPER STRANDING 0.080 [2.03] O.D. PVC INSULATION - 2.01 [51.05] 6. P/N: W-500/2 20AWG TINNED COPPER STRANDING 0.156 [3.96] — 9.0 [228.6] 4 0.080 [2.03] O.D. PVC INSULATION 3.0 [76.2] 4 CENTER 0.15 [3.81] — 0.23 [5.72] — **–** 4.25 [107.95] – 5.1 [129.54] — CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. TOLERANCES ARE: FRACTIONS DECIMALS ANGLES APPROVALS DATE .XX ± DRAWN DESCRIPTION 4/19 R.L. .XXX ± BNC MALE BREAKOUT TO APPROVED BY MATERIAL SEE NOTE. MINIHOOK LEADS SIZE CODE IDENT NO. DRAWING NO. FINISH B | 08505 | SEE NOTE. **NEXT ASSY** USED ON SCALE APPLICATION DO NOT SCALE DRAWING SHEET 1 OF 1