DESCRIPTION DATE APPROVED LTR NOTES: UNLESS OTHERWISE SPECIFIED 1. CONSTRUCTION: HOUSING: MOLDED NYLON. AVAILABLE IN BLACK, RED, GREEN OR BLUE. CONTACT TIP: NICKEL PLATED STEEL. 2. PERFORMANCE: MAXIMUM CURRENT: 10 AMPS MAXIMUM VOLTAGE: 1000 V MAXIMUM TEMPERATURE: 200°F (93°C) **-** 5.75 [145.97] -Ø0.875 [Ø22.23] 1.560 [39.62] 0.08 [2.01] **⊸** 0.350 [8.89] Ø0.175 [Ø4.45] WIRE EXIT HOLE SOLDER TAB - FRONT TIP & INSULATOR ASSEMBLY WIRE ATTACHMENT HELD IN PLACE BY A PRESS FIT. CONTRACT NO. UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. DATE APPROVALS .XX ± DRAWN DESCRIPTION R.L. 3/15 STD PIN TIP PROBE APPROVED BY MATERIAL SEE NOTE. FINISH SIZE CODE IDENT NO. DRAWING NO. REV. B | 08505 | 30 SEE NOTE. NEXT ASSY USED ON SCALE APPLICATION DO NOT SCALE DRAWING 1:1 SHEET 1 OF 1 THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.
MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.

REVISIONS