REVISIONS DESCRIPTION APPROVED LTR DATE NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 9230 BODY & FITTINGS: BRASS. NICKEL PLATED. PIN: BRASS. GOLD PLATED. DIELECTRIC: PTFE. 2. P/N: 0482 & P/N: 0148/0 & P/N: 0581 HOUSING: BLK MOLDED DELRIN CONTACT: GOLD PLATED BeCu HEAT SHRINK: BLK HEAT SHRINK 3. P/N: XHBLK HOUSING: BLK MOLDED NYLON. CONTACT: NICKEL SILVER ALLOY. CENTER O O RED SPRING: STAINLESS STEEL GROUND O O BLACK 4. P/N: XHLRED WIRING SCHEMATIC HOUSING: RED MOLDED NYLON. CONTACT: NICKEL SILVER ALLOY. SPRING: STAINLESS STEEL 5. P/N: W-600/0 **—** 3.3 [82.55] 18AWG TINNED COPPER STRANDING 0.144 [3.66] O.D. PVC INSULATION 1.7 [42.16] -6. P/N: W-600/2 18AWG TINNED COPPER STRANDING 0.144 [3.66] O.D. PVC INSULATION **-** 1.69 [42.95] **→** 0.275 [6.98] 9.0 [228.6] 3.0 [76.2] -/4\CENTER CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. TOLERANCES ARE: FRACTIONS DECIMALS ANGLES APPROVALS DATE .XX ± DRAWN DESCRIPTION 4/19 R.L. .XXX ± BNC FEMALE BREAKOUT TO APPROVED BY MATERIAL SEE NOTE. 18AWG XH/XHL MACROHOOK LEADS SIZE CODE IDENT NO. DRAWING NO. FINISH B 08505 SEE NOTE. **NEXT ASSY** USED ON SCALE APPLICATION DO NOT SCALE DRAWING SHEET 1 OF 1 THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK, THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.

MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT, MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.