REVISIONS DESCRIPTION APPROVED LTR DATE NOTES: UNLESS OTHERWISE SPECIFIED 1. P/N: 9267-0002 & P/N: 0344 BODY & FITTINGS: NICKEL PLATED BRASS CONTACT: GOLD PLATED BRASS. DIELECTRIC: PTFE SPRING: NICKEL PLATED SK5 SPRING: RED RUBBER WASHER: COPPER, TIN, NICKEL PLATED CSR 2. P/N: 0480 & P/N: 0148/0 & P/N: 0581 HOUSING: BLK MOLDED DELRIN CONTACT: GOLD PLATED BeCu HEAT SHRINK: BLK HEAT SHRINK CENTER O O RED 3. P/N: 9203BLK GROUND O O BLACK HOUSING: BLK MOLDED NYLON. FRAME: NICKEL PLATED BRASS. WIRING SCHEMATIC CONTACT: NICKEL PLATED BeCu OR PHOSPHOR BRONZE. 4. P/N: 9203RED **←** 1.61 [40.89] **←** HOUSING: RED MOLDED NYLON. FRAME: NICKEL PLATED BRASS. CONTACT: NICKEL PLATED BeCu OR PHOSPHOR BRONZE. -/3\GROUND 5. P/N: W-500/0 - 0.735 [18.67] 20AWG TINNED COPPER STRANDING 0.080 [2.03] O.D. PVC INSULATION 6. P/N: W-500/2 20AWG TINNED COPPER STRANDING 0.160 [4.06] 2.01 [51.05] 0.080 [2.03] O.D. PVC INSULATION STD BAN SKT 0.175 [4.45] -≠ 4.0 [101.60] ≠ ≠ 4.0 [101.60] *≠* CENTER CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. TOLERANCES ARE: FRACTIONS DECIMALS ANGLES APPROVALS DATE .XX ± DRAWN DESCRIPTION 4/19 R.L. .XXX ± BNC MALE BREAKOUT TO 4" APPROVED BY MATERIAL SEE NOTE. 9203 STK STD BAN PLUG LEADS SIZE | CODE IDENT NO. | DRAWING NO. FINISH REV. SEE NOTE. B | 08505 | **NEXT ASSY** USED ON SCALE APPLICATION DO NOT SCALE DRAWING SHEET 1 OF THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.
MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.