


NOTES: UNLESS OTHERWISE SPECIFIED

1. P/N: XMCOLOR
HOUSING & PLUNGER: MOLDED NYLON. AVAILABLE IN TEN COLORS.
CONTACT BLADE: GOLD PLATED BeCu.
SPRING: STAINLESS STEEL.
2. P/N: 9265-HS
INSULATOR: HEAT SHRINK TUBING. BLACK.
BODY & CONTACT : GOLD PLATED BRASS.
3. P/N: W-200/COLOR
22AWG TINNED COPPER
0.070 [1.78] O.D. PVC INSULATION
AVAILABLE IN TEN COLORS.
4. PERFORMANCE
MAXIMUM CURRENT: 2.5 AMPS
MAXIMUM VOLTAGE: HANDHELD: 33VAC/60VDC
HANDS FREE: 1000 W.V.D.C.
MAXIMUM TEMPERATURE: 176°F (80°C)

LTR	REVISIONS		DATE	APPROVED
	DESCRIPTION			



		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ± ± .XXX ±	CONTRACT NO.		E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.
			APPROVALS	DATE	
		MATERIAL SEE NOTE.	DRAWN	R.L.	5/13
			APPROVED BY		
		FINISH SEE NOTE.	DESCRIPTION		
			MICRO-HOOK (XM) TO 0.025 [0.64] PIN PLUG (9265-HS)		
NEXT ASSY	USED ON		SIZE	CODE IDENT NO.	DRAWING NO.
			B	08505	230XM
APPLICATION		DO NOT SCALE DRAWING	SCALE	1:1	SHEET 1 OF 1