
REVISIONS LTR DESCRIPTION DATE APPROVED NOTES: UNLESS OTHERWISE SPECIFIED 1. AVAILABLE IN: 25 FT, 50 FT, 100FT, 500FT, AND 1,000 FT **SPOOLS**

2. PERFORMANCE:

MAXIMUM VOLTAGE: HANDHELD: 33VAC/60VDC

HANDS FREE: 1000 W.V.D.C.

MAXIMUM TEMPERATURE: 221°F (105°C)



• ACTUAL SIZE

		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± N/A .XX ± N/A ± N/A	CONTRACT NO. APPROVALS DRAWN	DATE	E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.
		.xxx ± 0.006 MATERIAL WIRE: TINNED COPPER	R.L. APPROVED BY	7/15	18 AWG 65X36 TINNED
		INSULATION: PVC FINISH AVAILABLE IN ALL TEN			COPPER, PVC INSULATED WIRE SIZE CODE IDENT NO. DRAWING NO. REV.
NEXT ASSY	USED ON	COLORS.			A 08505 9506
APPLICATION		DO NOT SCALE DRAWING			SCALE 10:1 SHEET 1 OF 1