


NOTES: UNLESS OTHERWISE SPECIFIED

1. P/N: 9275COLOR  
INSULATOR: MOLDED PVC. AVAILABLE IN TEN COLORS.  
ALLIGATOR: NICKEL PLATED STEEL.
2. P/N: 9209COLOR  
INSULATOR: MOLDED PVC. AVAILABLE IN RED  
FRAME: TIN PLATED COPPER.
3. P/N: W-200/COLOR  
22AWG 65X40 TINNED COPPER  
0.070 [1.78] O.D. PVC INSULATION  
AVAILABLE IN TEN COLORS.
4. PERFORMANCE  
MAXIMUM CURRENT: 2.5 AMPS  
MAXIMUM VOLTAGE: 1000 W.V.D.C.  
MAXIMUM TEMPERATURE: 221°F (105°C)

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED



		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ± ± .XXX ±	CONTRACT NO.		<div><div>E-Z-HOOK®</div><div>DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.</div></div>			
			APPROVALS	DATE	DESCRIPTION			
			DRAWN R.L.	10/12				
		MATERIAL SEE NOTE.	APPROVED BY		MINI ALLIGATOR CLIP (9275) TO 0.14 [3.57] INSLTD SPADE LUG (9209)			
		FINISH SEE NOTE.			SIZE	CODE IDENT NO.	DRAWING NO.	REV.
NEXT ASSY	USED ON				B	08505	289M	
APPLICATION		DO NOT SCALE DRAWING			SCALE	1:1		SHEET 1 OF 1