DESCRIPTION DATE APPROVEI LTR NOTES: UNLESS OTHERWISE SPECIFIED 1. CONSTRUCTION: SLIDE: MOLDED NYLON. AVAILABLE IN TEN COLORS. CONTACT BLADE: NICKEL SILVER SPRING: STAINLESS STEEL 2. PERFORMANCE: MAXIMUM CURRENT: 5 AMPS MAXIMUM VOLTAGE: 0 V MAXIMUM TEMPERATURE: 200°F (93°C) 0.18 [4.57] -Ø0.105 [Ø2.67] MAX. CONNECTION - 0.395 [10.03] **-** 0.156 [3.96] 3. INSTALLATION TOOL P/N T-20 DIA. 0.360 [9.14] 0.120 [3.05] 1.475 [37.47] HOOK DETAIL SCALE: 4:1 0.615 [15.62] 0.490 [12.45] 0.023 [0.57] --CONTRACT NO. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: E-Z-HOOK DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A. FRACTIONS DECIMALS ANGLES DATE APPROVALS DRAWN 7/06 R.L. .XXX ± E-Z-NAIL CLIP MULTIPLE APPROVED BY MATERIAL SEE NOTE. ACTUAL SIZE TERMINAL FINISH SIZE CODE IDENT NO. DRAWING NO. SEE NOTE. **|08505**|83-8 **NEXT ASSY USED ON** SCALE **APPLICATION** DO NOT SCALE DRAWING SHEET 1 OF 1 THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK, DIV. OF TEKTEST INC.
MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.