Easy plug and play diagnostic testing with adapters that can all connect to the test leads in kit.

Application:

Reliable test lead kit designed for a variety of electronic, automotive, and industrial measurement applications. Expand your testing capabilities and provide accurate readings. All of these parts can fit together for plug and play diagnostics with interchangeable parts via the banana plug test leads to banana socket adapters to conform to multiple testing requirements.

Features & Benefits:

Insulation-piercing hooks make non-invasive contact instantly without having to strip wire in hard to reach wires. Easily grab the exact wire you want to test with the slim chisel-tip design, seat it within the V-groove design of the tip which centers the wire prior to piercing ensuring the needle makes contact on the first try, and obtain instant continuity by activating the piercing needle.

Comprehensive collection of the most widely used test connectors for automotive diagnostic work in one kit. All parts contain banana sockets for easy connection to banana plug test leads.

Banana plugs securely plug into hand-held digital multimeter's for diagnostic work.
Compatible with DMMs and most other

testing equipment.

Provide technicians extensions for any applications with the test leads that include short and extra-long length banana plug jumpers that helps extend testing from the front to the back of a vehicle.



Flexible diagnostic testing made easy.

Tech Specs:

*Part numbers are in parentheses (). R/B is a set of 2, 1 red and 1 black.

Included: 1 R/B 36" lead (9183/9898) 1 black 144" lead (9183/9898) 1 R/B standard alligator (8016) 1 red test hook (XEL) 1 red test probe (31)	Test Leads: 18 AWG; PVC or Silicone insulation; 65 x 36 tinned copper stranding; connects to standard banana sockets; straight style accepts both (un)shrouded
Packaging: 1.5 lbs., 9.5" x 6.4" x 2.3" case with foam padding	Test Probe: 0.08" (2 mm) pin tip diameter; connects to unshrouded standard banana plugs
Test Hook: pierces most 28-14 AWG wire or a max 0.15" wire dia.; 2 shrouded banana sockets in T-handle; connects to both (un)shrouded standard plugs	Alligator Clips: standard - 0.31" max jaw opening; connects to standard unshrouded plugs

Competitively priced with quality materials. Made in the USA since 1956. Also sold separately, in more lengths & colors.